



COLOR QUICK-DRYING LACQUER

AREA OF APPLICATION

For the protection of different wooden surfaces, as well as veneered and massive furniture indoors, when you want to achieve a visible structure of wood.

PROPERTIES

- colourless top coat
- quick-drying
- good hardness
- does not become yellow
- no unpleasant odours

TECHNICAL DATA	
COMPOSITION	Acrylic binder, water, additives
COLOR SHADES	Colourless
TINTING	/
GLOSS	Glossy, semi-matt
DENSITY	1,0 - 1,1 g/ml
THINNING	Water, up to 10%
EU VOC category and limits	IIA(e), 130 g/l (2010); the product contains: max. 75 g/l
PACKAGING UNITS	0.75 l
SHELF LIFE	The shelf life of an originally sealed and suitably stored product (temperature ranging from +5 °C to +35 °C, in dry place) is indicated on the packaging. MUST NOT FREEZE.

INSTRUCTIONS FOR USE				
APPLICATION METHOD	Thinning	Viscosity (DIN 4 mm)	Nozzle	Pressure
brush (artificial fibers)	as required	/		
spraying	Max. 10%	/	1,2 - 1,5 mm	2 - 3 bar
WORKING CONDITIONS	Paint, air and surface temperature should be at least +15° C, and rel. air humidity under 75%			
DRYING (T = +20° C, rel. humidity 65%)	Dry dust-free in approx. 1 hour, feels dry in 2 - 3 hours, apply the following layer after 4 hours At lower temperatures and higher relative humidity the drying time is extended.			
COVERAGE	Theoretically: 8 - 10 m ² with 1 l and one application The actual consumption depends on wood treatment, the type of wood and the quality of application.			
CLEANING TOOLS	Immediately after use			

SURFACE PREPARATION

1. Wooden surface

The humidity must not exceed 15% for coniferous trees, and 12% for deciduous trees. The dry surface is to be sanded and cleaned, and any wax, resin or grease should be removed with **COLOR NITRO THINNER**.

2. Renovation of old coating

Undamaged coatings are to be cleaned and sanded, damaged coatings are to be removed completely.

COATING SYSTEMS

SURFACE		SURFACE PREPARATION	PRIMER	TOP COAT
WOOD	indoor	sanding removing impurities	1 - 2x COLOR QUICK-DRYING PRIMING LACQUER	1 - 2x COLOR QUICK-DRYING LACQUER

VII-2024





OLD COATINGS	indoor	cleaning, sanding and removing damaged coatings	/	2x COLOR QUICK-DRYING LACQUER
--------------	--------	---	---	---

NOTES AND SPECIAL FEATURES

- In case working temperature is lower than +15 °C, the coating film will not be formed.